WALKER TAPE®

Safety Data Sheet

Issue Date: 18-Sep-2013 **Revision Date:** 25-Mar-2025 **Version** 2

1. IDENTIFICATION

Product identifier
Product Name Mity-Tite

Other means of identification
SDS # WTC-011

UN/ID No UN1133

Recommended use of the chemical and restrictions on use
Recommended Use Adhesives.

Details of the supplier of the safety data sheet
Supplier Address
Walker Tape Co., Inc
9312 Prosperity Rd
West Jordan, Utah 84081

Emergency telephone number
Company Phone Number Phone: (801) 282-2015
Fax: (801) 282-2131
Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Moderately viscous, clear liquid **Physical state** Liquid **Odor** Characteristic Hydrocarbon Ester

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 2

Signal word
Danger

Hazard statements
Harmful if inhaled
Causes serious eye irritation
May cause cancer
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
Highly flammable liquid and vapor

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/clothing and eye/face protection
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground and bond container and receiving equipment
Use explosion-proof electrical/ ventilating / lighting/ equipment
Use only non-sparking tools
Take action to prevent static discharges
Keep cool

Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
IF INHALED: Remove person to fresh air and keep comfortable for breathing
In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage
Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Other hazards
Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Ethyl acetate	141-78-6	30-60
Isopropanol	67-63-0	10-30
Heptane, branched, cyclic and linear	426260-76-6	10-30
Toluene	108-88-3	1-5
Vinyl acetate	108-05-4	0.1-1
Tert-pentyl peroxypivalate	29240-17-3	0.1-1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If easy to do, remove contact lenses. Immediately call a poison center or doctor/physician.

Skin Contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Wash skin with soap and water. If irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, give oxygen. If breathing is irregular or stopped, administer artificial respiration. Get medical attention.

Ingestion IF SWALLOWED: call a poison control center or physician immediately. Do NOT induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Have patient lie down and keep warm.

Most important symptoms and effects, both acute and delayed

Symptoms Causes serious eye irritation. Causes skin irritation. Repeated, frequent or prolonged contact with skin may cause defatting of the skin which can lead to irritation, defatting and/or dermatitis. May cause respiratory irritation. May cause drowsiness or dizziness. Irritating to mouth, throat, and stomach if ingested. Liquid ingestion may result in vomiting; aspiration of liquid into the lungs must be avoided as liquid contact with the lungs can result in chemical pneumonitis and pulmonary edema/hemorrhage.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical. Water spray (fog). Alcohol resistant foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Extremely flammable. Vapors are heavier than air and may travel along ground to ignition sources and flash back. May generate toxic or irritating combustion products.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2). Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of nitrogen and sulfur may also be formed.

Explosion data

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Water may be used to cool containers to prevent pressure build up.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Isolate hazard area. Keep unnecessary and unprotected personnel from entering.

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Small Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. For large spills, dike far ahead of spill for later disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharges. Use with local exhaust ventilation.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Store at room temperature.

Incompatible Materials Strong oxidizing agents. Acids. Bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Ethyl acetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m^3 (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m^3	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m^3
Isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m^3 (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m^3 (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m^3	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m^3 STEL: 500 ppm STEL: 1225 mg/m^3

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Toluene 108-88-3	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m^3 (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m^3 Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m^3 STEL: 150 ppm STEL: 560 mg/m^3
Vinyl acetate 108-05-4	STEL: 15 ppm TWA: 10 ppm	(vacated) TWA: 10 ppm (vacated) TWA: 30 mg/m^3 (vacated) STEL: 20 ppm (vacated) STEL: 60 mg/m^3	Ceiling: 4 ppm 15 min Ceiling: 15 mg/m^3 15 min

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Explosion-proof general and local exhaust ventilation. Eyewash stations. Showers.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Chemical anti-splash safety goggles.

Skin and Body Protection Neoprene or rubber gloves with cuffs. Wear suitable protective clothing. Wash contaminated clothing, including shoes, before reuse.

Respiratory Protection Ensure adequate ventilation, especially in confined areas. In case of inadequate ventilation wear respiratory protection.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash face, hands and any exposed skin thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid		
Appearance	Moderately viscous, clear liquid	**Odor**	Characteristic Hydrocarbon Ester
Color	Not determined	**Odor Threshold**	Not determined

Property	Values	Remarks • Method
pH	Not available	
Melting point / freezing point	Not available	
Initial boiling point and boiling range	65 °C / 150 °F	
Flash point	< 20 °C / < 68 °F	(ASTM D6450)
Evaporation rate	> 1	N-butyl acetate
Flammability (Solid, Gas)	Liquid-not applicable	
Flammability Limit in Air		
Upper flammability or explosive limits	13%	
Lower flammability or explosive limits	1.3%	
Vapor Pressure	180 mmHg	@ .? °C
Relative vapor density	~3	.? (air = 1)
Relative Density	0.840	@ 60°F (ASTM D 1298)
Water Solubility	Slightly soluble	
Solubility in other solvents	Not determined	
Partition Coefficient	Not applicable	
Autoignition temperature	Not available	
Decomposition temperature	Not determined	

Property	Values	Remarks • Method
Kinematic viscosity	Not determined	
Dynamic viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not applicable	

Other information

VOC Content	3.85 lb/gal (462 g/L)
Bulk density	7.0 lb/gal

10. STABILITY AND REACTIVITY

Reactivity
Not reactive under normal conditions.

Chemical stability
Stable under recommended storage conditions.

Possibility of hazardous reactions
None under normal processing.

Conditions to Avoid
Keep out of reach of children.

Incompatible materials
Strong oxidizing agents. Acids. Bases.

Hazardous decomposition products
Carbon monoxide. Carbon dioxide (CO2). Various unidentified organic compounds.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact Avoid contact with skin.

Inhalation May be harmful if inhaled.

Ingestion May be harmful if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl acetate 141-78-6	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit)	= 4000 ppm (Rat) 4 h
Isopropanol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	> 10000 ppm (Rat) 6 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
Vinyl acetate 108-05-4	= 2900 mg/kg (Rat)	= 2335 mg/kg (Rabbit)	= 3680 ppm (Rat) 4 h
Tert-pentyl peroxypivalate 29240-17-3	-	= 2000 mg/kg (Rabbit)	> 9500 mg/m^3 (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes mild skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Carcinogenicity May cause cancer.

Chemical name	ACGIH	IARC	NTP	OSHA
Isopropanol 67-63-0		Group 3		X
Toluene 108-88-3		Group 3		
Vinyl acetate 108-05-4	A3	Group 2B		X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans
Group 3 IARC components are "not classifiable as human carcinogens"
Occupational Safety and Health Administration of the US Department of Labor
X - Present

Reproductive toxicity Suspected of damaging fertility or the unborn child.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 4,841.00 mg/kg
ATEmix (dermal) 13,280.40 mg/kg
ATEmix (inhalation-gas) 4,199.40 ppm
ATEmix (inhalation-dust/mist) 75.00 mg/l
ATEmix (inhalation-vapor) 20.10 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Ethyl acetate 141-78-6		LC50: 220 - 250mg/L (96h, Pimephales promelas) LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss)	EC50: =560mg/L (48h, Daphnia magna)

Chemical name	Algae/aquatic plants	Fish	Crustacea
Isopropanol 67-63-0	EC50: >1000mg/L (96h, Desmodesmus subspicatus) EC50: >1000mg/L (72h, Desmodesmus subspicatus)	LC50: =9640mg/L (96h, Pimephales promelas) LC50: =11130mg/L (96h, Pimephales promelas) LC50: >1400000µg/L (96h, Lepomis macrochirus)	EC50: =13299mg/L (48h, Daphnia magna)
Toluene 108-88-3	EC50: >433mg/L (96h, Pseudokirchneriella subcapitata) EC50: =12.5mg/L (72h, Pseudokirchneriella subcapitata)	LC50: 15.22 - 19.05mg/L (96h, Pimephales promelas) LC50: =12.6mg/L (96h, Pimephales promelas) LC50: 5.89 - 7.81mg/L (96h, Oncorhynchus mykiss) LC50: 14.1 - 17.16mg/L (96h, Oncorhynchus mykiss) LC50: =5.8mg/L (96h, Oncorhynchus mykiss) LC50: 11.0 - 15.0mg/L (96h, Lepomis macrochirus) LC50: =54mg/L (96h, Oryzias latipes) LC50: =28.2mg/L (96h, Poecilia reticulata) LC50: 50.87 - 70.34mg/L (96h, Poecilia reticulata)	EC50: 5.46 - 9.83mg/L (48h, Daphnia magna) EC50: =11.5mg/L (48h, Daphnia magna)
Vinyl acetate 108-05-4		LC50: =14mg/L (96h, Pimephales promelas) LC50: 15.04 - 21.54mg/L (96h, Lepomis macrochirus) LC50: 26.1 - 36.63mg/L (96h, Poecilia reticulata)	

Persistence/Degradability
Not determined.

Bioaccumulation
There is no data for this product.

Mobility

Chemical name	Partition coefficient
Ethyl acetate 141-78-6	0.73
Isopropanol 67-63-0	0.05
Toluene 108-88-3	2.73
Vinyl acetate 108-05-4	0.73
Tert-pentyl peroxypivalate 29240-17-3	3.3

Other adverse effects
Not determined

13. DISPOSAL CONSIDERATIONS

Disposal methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethyl acetate 141-78-6		Included in waste stream: F039		U112
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

California Hazardous Waste Status

Chemical name	California Hazardous Waste Status
Ethyl acetate 141-78-6	Toxic Ignitable
Isopropanol 67-63-0	Toxic Ignitable
Toluene 108-88-3	Toxic Ignitable
Vinyl acetate 108-05-4	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1133
Proper Shipping Name Adhesives
Transport hazard class(es) 3
Packing Group II
Reportable Quantity (RQ) 1000 lb

IATA

UN number or ID number UN1133
Proper Shipping Name Adhesives
Transport hazard class(es) 3
Packing group II

IMDG

UN number or ID number	UN1133
Proper Shipping Name	Adhesives
Transport hazard class(es)	3
Packing Group	II
Marine Pollutant	This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AIIC
Ethyl acetate	X	ACTIVE	X	X	X	X	X	X	X
Heptane, branched, cyclic and linear	X	ACTIVE	X					X	
Isopropanol	X	ACTIVE	X	X	X	X	X	X	X
Toluene	X	ACTIVE	X	X	X	X	X	X	X
Vinyl acetate	X	ACTIVE	X	X	X	X	X	X	X
Tert-pentyl peroxypivalate	X	ACTIVE	X	X		X		X	X

Legend:

TSCA *- United States Toxic Substances Control Act Section 8(b) Inventory*

DSL/NDSL *- Canadian Domestic Substances List/Non-Domestic Substances List*

EINECS/ELINCS *- European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*

ENCS *- Japan Existing and New Chemical Substances*

IECSC *- China Inventory of Existing Chemical Substances*

KECL *- Korean Existing Chemicals Inventory*

PICCS *- Philippines Inventory of Chemicals and Chemical Substances*

AICS *- Australian Inventory of Chemical Substances*

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Ethyl acetate 141-78-6	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Vinyl acetate 108-05-4	5000 lb	5000 lb	RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Isopropanol - 67-63-0	67-63-0	10-30	1.0
Toluene - 108-88-3	108-88-3	1-5	1.0
Vinyl acetate - 108-05-4	108-05-4	0.1-1	0.1

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene	1000 lb	X	X	X
Vinyl acetate	5000 lb			X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Toluene - 108-88-3	Developmental

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Ethyl acetate 141-78-6	X	X	X
Isopropanol 67-63-0	X	X	X
Toluene 108-88-3	X	X	X
Vinyl acetate 108-05-4	X	X	X

16. OTHER INFORMATION

NFPA	**Health hazards**	**Flammability**	**Instability**	**Special hazards**
	-	-	0	-
HMIS	**Health hazards**	**Flammability**	**Physical hazards**	**Personal Protection**
	-	-	-	Not determined

Issue Date: 18-Sep-2013
Revision Date: 25-Mar-2025
Revision Note: Updated formula

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet